

注塑用机械手

TAKE-OUT ROBOT

MBW-200



标准功能 STANDARD FUNCTION

- 装箱动作 (多轴256点)
Packaging motion (Max. 256 points)
- 自由摆荡点 (115点 × 2轴)
Free swinging motion (115points × 2stage)
- 取出侧进姿势控制
Forward and rotate at removing side
- 行走途中姿势
Posture control during traverse
- 落下侧下途中姿势
Posture midway descent at release side
- 顶针连动
Ejector link
- 不良品排出回路
Defective product reject circuit
- 初期不良品排出回路
Initial defective product reject circuit
- 取出下降待机
Delayed arm descent
- 胶口途中开放 (去程, 返程)
Midway runner release (Move, Revert)
- 水口横内开放
Runner release within mold
- 吸着确认单元 (2回路)
Additional vacuum sensing unit (2 circuit)
- 横走行待机
Delayed traverse
- 溶胶取出回路
Unmelt extract circuit
- 输送带启动信号
Start signal of conveyor
- 内部存储器 (最大100种类型)
Internal memory (for Max100 molds)
- 设定值锁定功能
Lock function of setting value
- 固定可切换
Extraction from fixed mold
- 2国语言切换 (中文, 英文)
Two language exchange (Chinese/English)

型式 MODEL 单位 UNIT MBW-200

电源 Power Source	V	AC380 ± 10% 50/60Hz
最大消费电力 Max Power Consumption	KW	4.5
使用气压 Air Pressure	Mpa	0.5 ~ 0.7
空气消费量 Air Consumption	Nl/cycle	48
驱动方式 Drive System	---	伺服马达 / AC Servo Motor
姿势 (气缸) Posture (Air Cylinder)	---	90°固定 / 90°Fixed
气缸推力 (气压0.5MPa时) Air Cylinder Driving Force (Air Pressure at 0.5MPa)	Kg	50 (含夹具重量 / Incl Chuck Weight)
最大可搬重量 Max.Load	N · m	110
姿势力矩 Posture Torque	mm	2000/2500/3000
行程 Stroke	mm	---
主臂上下 Main-arm Vertical	mm	460 ~ 2300
副臂上下 Sub-arm Vertical	mm	3000/3500
前后 Crosswise	mm	---
走行 Traverse	mm	1820
本体重量 Net Weight	Kg	1.6
本体 Main Body	Kg	1.6
操作盒 Pendant	Kg	1.6

外形尺寸 OUTER DIMENSIONS

A 总高 Overall height	2290(2530)/(2270)mm
B 总长 Overall length	4040(4520)mm
C 走行行程 Traverse stroke	3000(3500)mm
D 主臂上下行程 Main-arm vertical stroke	2000 (2500)/(3000)mm
E 主臂上下待机 Main-arm vertical standby	240mm
F 夹具安装有效空间 Bottom of crosswise to chuck mount position	---
G 底座侧面-箱体末端 Base side face-Box end	535mm
H 副臂上下待机 Sub-arm vertical standby	---
I 主臂前进最大值 Main-arm reach max	2300mm
J 主臂前进最大行程 Main-arm crosswise stroke max	1800mm
K 主臂前后待机最小值 Main-arm crosswise standby min	460mm
L 主副臂接近最小值 Main/Sub-arm proximity min	---
M 副臂前进最大行程 Sub-arm crosswise stroke max	---
N 副臂前后待机最小值 Sub-arm crosswise standby min	---
O 前后臂末端-箱体末端 Crosswise arm end-Box end	2875mm

- 当尺寸C是3000mm时, 尺寸为4040mm
- when dimension C is 3000mm, B is 4040mm
- 当尺寸D是2000mm时, 尺寸为2290mm
- when dimension D is 2000mm, A is 2290mm
- 当尺寸D是3000mm时, 尺寸为2770mm
- when dimension D is 3000mm, A is 2770mm

- 当尺寸C是3500mm时, 尺寸为4520mm
- when dimension C is 3500mm, B is 4520mm
- 当尺寸D是2500mm时, 尺寸为2530mm
- when dimension D is 2500mm, A is 2530mm

选项功能 OPTION FUNCTION

- ◆ 夹具内剪刀回路
Air nipper in chuck circuit
- ◆ NT剪切-可动侧
NT gate cutting on crossmember of moving
- ◆ 吸着确认回路
Additional vacuum sensing unit (4 circuits)
- ◆ 制品夹取回路
Product gripping 4 circuits
- ◆ 上升途中锁模
Mold close during ascend
- ◆ 回转单元
Rotation unit
- ◆ 顶针后退连动
Ejector return link
- ◆ 欧规12
EUROMAP12
- ◆ 欧规67
EUROMAP 67

